

REV. 2025.1 · 2025 EDITION

Care & cleaning guide

Daily cleaning, recommended products and what to avoid for each material.

CERAMIC SLABS

INSTALLATION

- Handle slabs with suction cups and frame; never upright without continuous support.
- Apply double-buttering with C2TE S1 adhesive and a 10 mm notched trowel on substrate and piece.
- Respect a minimum 2 mm joint indoors and expansion joints every 25 m² or 6 linear metres.
- On-site cuts are made with a water-cooled continuous diamond disc.

CARE & MAINTENANCE

- Daily cleaning with warm water and neutral detergent; rinse and dry to avoid limescale marks.
- Avoid strong acids (hydrofluoric) and metal scourers on polished finishes.
- Dried stains are removed with an alkaline cleaner and a soft-bristle brush.

PORCELAIN TILES

INSTALLATION

- Check substrate flatness (± 3 mm in 2 m) before laying.
- C2 S1 adhesive; double-buttering mandatory on 60×120 and larger formats.
- Minimum joint of 2 mm indoors and 5 mm outdoors; 20 mm pieces laid dry on pedestals or gravel.

CARE & MAINTENANCE

- Daily cleaning with warm water and neutral detergent; rinse and dry to avoid limescale marks.
- Avoid strong acids (hydrofluoric) and metal scourers on polished finishes.
- Dried stains are removed with an alkaline cleaner and a soft-bristle brush.

WASHBASINS

INSTALLATION

- A cut-out template for the worktop is supplied; central Ø 70 mm hole for the drain.
- Bed on a bead of neutral silicone; do not tighten the waste beyond 12 Nm.
- Check level before the silicone cures (24 h).

CARE & MAINTENANCE

- Clean with a microfibre cloth, water and neutral soap; do not use solvents or concentrated bleach.
- Surface marks are restored by gently sanding with 400 grit and applying polishing cream.
- Avoid prolonged contact with hair dyes or products with intense pigments.

TOILETS & SANITARYWARE

INSTALLATION

- Compatible with 1,150 mm frames; screw distance 180 mm.
- Horizontal Ø 100 mm outlet connection with elbow sleeve included.
- Fit the seat after curing and adjust the soft-close dampers.

CARE & MAINTENANCE

- The easy-clean glaze is maintained with standard non-abrasive cleaners.

- Check flush mechanisms and silicone joints annually.
- Do not use chlorine tablets in the cistern: they damage the internal mechanisms.

BATHROOM ACCESSORIES

INSTALLATION

- Concealed fixing with expansion anchors on ceramic slab: drill with a wet diamond bit.
- Check horizontality with a spirit level before sealing.
- No installation required.
- Place on a flat, dry surface.

CARE & MAINTENANCE

- Clean only with water and a soft cloth; dry after each use in hard-water areas.
- Do not use acidic, abrasive or concentrated descaling products on the PVD finish.
- Brushed bronze develops a natural patina that is part of the product's character.
- Clean with a microfibre cloth, water and neutral soap; do not use solvents or concentrated bleach.
- Surface marks are restored by gently sanding with 400 grit and applying polishing cream.
- Avoid prolonged contact with hair dyes or products with intense pigments.