

ALBA SERIES · REF. VN-TL-121

# Sal Marina

*The texture of lime render in rectified porcelain.*

Porcelain with a warm white ground and the irregular, luminous texture of traditional lime render. Conceived for bathroom and kitchen walls, it brings the light of a whitewashed house with the resilience of stoneware.

|              |                                                                 |
|--------------|-----------------------------------------------------------------|
| Category     | Porcelain tiles                                                 |
| Collection   | Alba                                                            |
| Sizes        | 60 × 120 cm (9 mm) · 60 × 60 cm (9 mm) · 30 × 60 cm (9 mm)      |
| Finishes     | Natural / Honed · Satin mineral                                 |
| Colours      | White                                                           |
| Applications | Bathrooms · Kitchens · Living spaces · Hospitality & commercial |
| Lead time    | In stock · 3 days                                               |

## KEY POINTS

- Diffused light: Satin surface that spreads light without glare.
- Three formats: Combinable in bond patterns for bathroom walls and floors.

## DIMENSIONS & WEIGHT

|               |                           |
|---------------|---------------------------|
| Formats       | 60×120 · 60×60 · 30×60 cm |
| Thicknesses   | 9 mm                      |
| Weight per m² | 21 kg                     |
| Edge          | Rectified, ±0.2 mm        |
| Bookmatch     | No                        |

## MATERIAL & PERFORMANCE

|                   |                               |
|-------------------|-------------------------------|
| Material          | Full-body technical porcelain |
| Water absorption  | <= 0,1 %                      |
| Breaking strength | >= 50 N/mm²                   |
| Frost resistance  | Yes                           |
| Reaction to fire  | A1                            |
| Thermal shock     | No damage (10 cycles)         |

## SURFACE & FINISH

|                     |                               |
|---------------------|-------------------------------|
| Slip resistance     | R10 (natural) · R9 (satinado) |
| Abrasion resistance | PEI 4                         |
| Stain resistance    | Class 5                       |
| Chemical resistance | Class A (UA / ULA)            |
| Colour stability    | No variation under light      |
| Surface hardness    | Mohs 7–8                      |

Indicative reference values (demonstration data).

## INSTALLATION

- Check substrate flatness ( $\pm 3$  mm in 2 m) before laying.
- C2 S1 adhesive; double-buttering mandatory on 60×120 and larger formats.
- Minimum joint of 2 mm indoors and 5 mm outdoors; 20 mm pieces laid dry on pedestals or gravel.

## CARE & MAINTENANCE

- Daily cleaning with warm water and neutral detergent; rinse and dry to avoid limescale marks.
- Avoid strong acids (hydrofluoric) and metal scourers on polished finishes.
- Dried stains are removed with an alkaline cleaner and a soft-bristle brush.