

TIERRA SERIES · REF. VN-SL-421

Tierra Ocre

The colour of fired clay in a continuous plane.

Slab in an earthy ochre tone with a light clay mottle that evokes the terracotta floors of country houses. Its natural finish absorbs afternoon light and pairs with pale woods, lime and bronze.

Category	Ceramic slabs
Collection	Tierra
Sizes	120 × 280 cm (6 / 12 mm) · 120 × 120 cm (6 mm) · 60 × 120 cm · 20 mm (Outdoor)
Finishes	Natural / Honed · Textured grip
Colours	Terracotta
Applications	Living spaces · Kitchens · Outdoor spaces · Hospitality & commercial
Lead time	In stock · 5 days

KEY POINTS

- Stable colour: Mineral pigments unaltered under intense solar radiation.
- Indoor-outdoor: Textured 20 mm version to extend the floor onto the terrace.

DIMENSIONS & WEIGHT

Formats	120×280 · 120×120 · 60×120 cm
Thicknesses	6 · 12 · 20 mm
Weight per m ²	14 kg (6 mm) · 46 kg (20 mm)
Edge	Rectified, ±0.2 mm
Bookmatch	No

MATERIAL & PERFORMANCE

Material	Full-body technical porcelain
Water absorption	<= 0,1 %
Breaking strength	>= 50 N/mm ²
Frost resistance	Yes
Reaction to fire	A1
Thermal shock	No damage (10 cycles)

SURFACE & FINISH

Slip resistance	R9 (natural) · R11 (texturizado)
Abrasion resistance	PEI 4
Stain resistance	Class 5
Chemical resistance	Class A (UA / ULA)
Colour stability	No variation under light

Surface hardness

Mohs 7–8

Indicative reference values (demonstration data).

INSTALLATION

- Handle slabs with suction cups and frame; never upright without continuous support.
- Apply double-buttering with C2TE S1 adhesive and a 10 mm notched trowel on substrate and piece.
- Respect a minimum 2 mm joint indoors and expansion joints every 25 m² or 6 linear metres.
- On-site cuts are made with a water-cooled continuous diamond disc.

CARE & MAINTENANCE

- Daily cleaning with warm water and neutral detergent; rinse and dry to avoid limescale marks.
- Avoid strong acids (hydrofluoric) and metal scourers on polished finishes.
- Dried stains are removed with an alkaline cleaner and a soft-bristle brush.